What is claimed is:

- 1. A thermoplastic resin composition comprising 2.5 to 15 wt% of a thermoplastic elastomer and 85 to 97.5 wt% of tungsten powder.
- 2. The thermoplastic resin composition of claim 1, wherein the thermoplastic elastomer is a styrene-based thermoplastic elastomer.
- 3. The thermoplastic resin composition of claim 2, wherein the styrene-based thermoplastic elastomer is at least one styrene-based thermoplastic elastomer selected from the group consisting of a hydrogenated polystyrene-polyisoprene block copolymer, a hydrogenated polystyrene-polybutadiene block copolymer and a hydrogenated polystyrene-polyisoprene block copolymer containing a butadiene unit in a polyisoprene moiety.
- 4. A thermoplastic resin molded article comprising 2.5 to 15 wt% of a thermoplastic elastomer and 85 to 97.5 wt% of tungsten powder.
- 5. The molded article of claim 4, wherein a surface hardness of the molded article is 80 or less, when measured by a method defined in JIS K-7215.
- 6. The molded article of claim 4, wherein a specific gravity of the molded article is 8 or more.
- 7. The molded article of claim 5, wherein a specific gravity of the molded article is 8 or more.

- 8. The molded article of claim 4, wherein the thermoplastic elastomer is a styrene-based thermoplastic elastomer.
- 9. The molded article of claim 8, wherein a surface hardness of the molded article is 80 or less, when measured by a method defined in JIS K-7215.
- 10. The molded article of claim 8, wherein a specific gravity of the molded article is 8 or more.
- 11. The molded article of claim 9, wherein a specific gravity of the molded article is 8 or more.
- 12. The molded article of claim 8, wherein the styrene-based thermoplastic elastomer is at least one styrene-based thermoplastic elastomer selected from the group consisting of a hydrogenated polystyrene-polyisoprene block copolymer, a hydrogenated polystyrene-polybutadiene block copolymer and a hydrogenated polystyrene-polyisoprene block copolymer containing a butadiene unit in a polyisoprene moiety.
- 13. The molded article of claim 8, wherein a surface hardness of the molded article is 80 or less, when measured by a method defined in JIS K-7215.
- 14. The molded article of claim 8, wherein a specific gravity of the molded article is 8 or more.
- 15. The molded article of claim 9, wherein a specific gravity of the

molded article is 8 or more.